

FreePBX Beispielkonfiguration

12/04/2024 21:45:54

[FAQ Article Print](#)

Category:	Telefonanlagen (TVA/PBX mit e-fon Adapt)::FreePBX	Votes:	0
State:	public (all)	Result:	0.00 %
Language:	en	Last update:	03/07/2016 10:58:45

Symptom (public)

Problem (public)

Solution (public)

ACHTUNG: Diese Anleitung ist bereits älter und kann teilweise nur noch auf ältere Versionen von FreePBX angewandt werden.
-> Bitte kontrollieren Sie ebenfalls die weitere FAQ Einträge unter FreePBX im e-fon Support-Center

Author: Severin Meyer, BitWorld GmbH

- General Settings

- Trunk Name: 0719000000_efon

- Outbound CallerID: 0719000000

- CID Options: Allow Any CID

- Maximum Channels: 3

- Outgoing Settings

- Trunk Name: 0719000000_trunk

- Peer Details:

- context=custom-get-did-from-sip-x-number

- username=0719000000

- secret=sippasswordfromprovider

- fromuser=0719000000

- fromdomain=adapt.e-fon.ch

- type=friend

- insecure=very

- host=adapt.e-fon.ch

- disallow=all

- allow=alaw

- 0719000000:sippasswordfromprovider@adapt.e-fon.ch

- Inbound Routes

- 0719000000

- Description: Mainnumber

- DID Number: 0719000000

- Set Destination: <ring group or extension>

- 0719000001

- Description: DirectNumber1

- DID Number: 0719000001

- Set Destination: <ring group or extension>

- Outbound Routes

- Route Name: All

- Route CID:

- Dial Patterns: match pattern= 0X. -> The route will be used by all numbers with a leading 0.

- Trunk Sequence: 0: 0719000000_efon

- Asterisk changes:

- /etc/asterisk/extensions_custom.conf

[custom-get-did-from-sip-x-number]

exten => s,1,Goto(from-trunk,\${SIP_HEADER(X-Number)},1)

[macro-dialout-trunk-predial-hook]

;Add P-Preferred-Identity for the trunk CID 0719000000

exten => s,1,ExecIf(\$["\${TRUNKOUTCID}"] =

"0719000000"?SipAddHeader(P-Preferred-Identity:<sip:\${CALLERID(num)}@e-fon.ch>))